

FLOORING WOOD TO WOOD SCREW PH2, 4,2X55MM STAINLESS STEEL AISI 316 (A4)



42R55MX

APPLICATIONS

Wood-to-wood applications, subfloor

TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw head type	Small with 4 nibs
Screw recess	Phillips 2
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Stainless steel AISI 316 (A4)
Head diameter	7 mm
Point type	Type 17 cut point
Pointangle	23 °
Screw length	53.8 - 56.2 mm
Screw diameter	4.1 - 4.35 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274059297
Package quantity	1000 pieces
Net weight	3.79 kg

FASTENER SPECIFICATIONS



53.8 - 56.2 mm

4.1 - 4.35 mm

CE SPECIFICATIONS

Inner threaded diameter	3.15 mm
Threaded/profiled length	36 mm
Characteristic yield moment	2400 Nmm
Characteristic head pull through parameter	16 N/mm ²
Characteristic tensile capacity	3200 N
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.88 Nm
Characteristic torsional strength	3.47 Nm