



MAKE IT LAST.

KYOCERA SENCO UK Ltd.
630 Europa Boulevard
Gemini Business Park
Warrington WA5 7YH, United Kingdom
Tel: +44 (0) 1925 445566
info@kyocera-senco.co.uk
www.kyocera-senco.co.uk



DECLARATION OF PERFORMANCE 39JL035MPO (v5)

Name	Fiber screw Phosphated, Phillips 2, 3,9x35mm
Article number	39JL035MPO
GTIN	8715274307367

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco UK Ltd., 630 Europe Boulevard, Warrington WA5 7YH,UK
Intended use	Mechanical fastener
Unique identification code	39JL035MPO
DOP No	39JL035MPO
Designated standard	EN 14566:2008+A1:2009
AVCP	4

Declared performances	
Essential characteristics for: 39JL035MPO	Performance
Reaction to fire	A1
Flexural strength	Pass

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in England, Wales and Scotland (acc. to e Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and Construction Products (Amendment etc.) (EU Exit) Regulations 2020) under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO UK Ltd by:

Place and date of issue: Warrington, 02-06-2026

Lars Aa. Mortensen
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Screw diameter	d	3.9 mm
Head diameter	d_h	7 mm
Screw length	L	35 mm
Threaded/profiled length	l_g	27 mm
Inner threaded diameter	d_i	2.9 mm
Reaction to fire		A1