SENCO®
MAKE IT LAST.

USP CHIPBOARD SCREW COUNTERSUNK HEAD, POZIDRIV 2, 5,0X80MM

CARBON STEEL STANDARD TENSILE



32018050080

APPLICATIONS
Wood-to-wood applications, composite timbers

TECHNICAL SPECIFICATIONS

Screw head type	Countersunk
Screw recess	Pozidriv 2
Screw thread type	Partly threaded
Wire material	Carbon steel standard tensile
Finish	Clear zinc
Head diameter	10 mm
Point type	Sharp
Screw length	80 - 80 mm
Screw diameter	5 - 5 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274238708
Package quantity	200 pieces
Net weight	1.264 kg

FASTENER SPECIFICATIONS



80 - 80 mm

5 - 5 mm

CE SPECIFICATIONS

CE fastener type	Chipboard screw
Inner threaded diameter	3.05 mm
Threaded/profiled length	50 mm
Characteristic yield moment	5500 Nmm
Characteristic head pull through parameter	14 N/mm²
Characteristic tensile capacity	7000 N
Torsional ratio	≥1.5
Characteristic torsional resistance	6 Nm
Characteristic torsional strength	6 Nm