



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.  
Pascallaan 88  
8218 NJ Lelystad, The Netherlands  
Tel: +31 (0)320 29 55 75  
info@kyocera-senco.eu  
www.kyocera-senco.eu



## DECLARATION OF PERFORMANCE NN24AABMR (v0)

Name	NN metalconnector ring 4,0x60mm
Article number	NN24AABMR
GTIN	8715274036540

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad
Intended use	Dowel-type fastener
Unique identification code	NN24AABMR
DOP No	NN24AABMR
Harmonized standard	EN 14592:2008+A1:2012
AVCP	3
NB	1686

Declared performances		
Essential characteristics for: NN24AABMR		Performance
Characteristic yield moment	$M_{y,k}$	6850 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	6,99 N/mm <sup>2</sup>
	$f_{head,k}$	NPD
Characteristic tensile capacity	$f_{tens,k}$	NPD
Durability against corrosion		Zinc Plated, SC 1, EN 1995-1-1

$f_{ax,k}$  en  $f_{head,k}$  are tested at a characteristic timber density of 350 kg/m<sup>3</sup>

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO Netherlands B.V. by:

Place and date of issue: Lelystad, 22-10-2024

Lars Aa. Mortensen  
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Nail diameter	$d$	4 mm
Head cross sectional area	$d_h$	50 mm
Nail length	$L$	60 mm
Threaded/profiled length	$l_g$	53 mm
Length of point	$L_p$	5,1 mm
Coating type	Type	Coating type 3
Reaction to fire		A1