



MAKE IT LAST.

PC1250, MIDI COMPRESSOR, 110V



PC1250UK1

The PC1250 compressor is designed to cover all onsite applications with pneumatic tooling. With its large 46L tank capacity this compressor is ideal for situations where minimal motor running is required, combined with the 2hp motor this compressor can provide 277L/min of air displacement.

APPLICATIONS

Anchors, asphalt shingles, baseliner, battens, butt joints, cabinets, casing, ceiling grid to concrete, corrugated box fastening, decking, decking soft wood, decorative trim, doors and windows, drywall, drywall track fastening, fencing, finish and trim, floor heating, framing, furnitures, grooved decking, haften to roof-fastenings, hardwood flooring, insulation boards, joist hangers, lathing, metal framing, moldings, nailing into masonry & steel, pallets and crates, paneling, picture frames, plastic membrane fixing, pre-drilled metal to wood applications, rebar tying, roof and wall felt, roofing, sheathing, siding, soffits, straps, subfloor, synthetic wrappings, tar paper, tin roofs, wire to wood stapling, wood-to-steel applications, wood-to-wood applications, zinc sheathing and coverings, haften, gutter, carton tube cap, carton box cover, felt, trusses, packaging, wood shingles, drawers, underlayment, lattice, baseboard, chairs, steel to steel, box assembly, furring, furniture framing, miter joints, exterior hard fiber to wood or light steel, insulation sheathing, bedding, planks, beams, boards, shoes, composite timbers, hinges, drywall to heavy steel, drywall to light steel, drywall to wood, wood construction, stairs, agriculture, gardening, hat channel, metal washers, fiber glass shingles, vapor barriers, ornamentals, pallets, crates, rafter joints, concrete forms, particle boards, exterior gypsum fiber board to wood or light steel, hanging hooks, upholstering, upholstery trim panels



2850 RPM/TPM

TECHNICAL SPECIFICATIONS

Oil free	Yes
Dimensions	880 x 320 x 670 mm
Net weight	42 kg
Electrical plug type	UK
Nominal power	1.5 kW
Voltage	110 V
Nominal power	2 HP
Tank Capacity	46 l
Max output pressure	10 bar
Air displacement	277 l/m
Airflow at 6 bar	164 l/m
Number of airoutlets	1 piece
Air outlet socket type	Universal coupler

IDENTIFICATION

Article number	PC1250UK1
GTIN	8715274045009