

FLOORING WOOD TO WOOD SCREW 4,2X55MM STAINLESS STEEL AISI 304 (A2)



42RH55MS-8014

APPLICATIONS

Wood-to-wood applications, subfloor


TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw head type	Small with 4 nibs
Screw recess	Senco drive 25
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Stainless steel AISI 304 (A2)
Head diameter	7 mm
Point type	Type 17 cut point
Point angle	23 °
Screw length	53.8 - 56.2 mm
Screw diameter	4.1 - 4.3 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274054384
Package quantity	1000 pieces
Net weight	3.72 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

Service class	3
Inner threaded diameter	3.15 mm
Threaded/profiled length	36 mm
Characteristic yield moment	2400 Nmm
Characteristic head pull through parameter	16 N/mm ²
Characteristic tensile capacity	3200 N
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.88 Nm
Characteristic torsional strength	3.47 Nm