



MAKE IT LAST.

KYOCERA SENCO UK Ltd.  
630 Europa Boulevard  
Gemini Business Park  
Warrington WA5 7YH, United Kingdom  
Tel: +44 (0) 1925 445566  
info@kyocera-senco.co.uk  
www.kyocera-senco.co.uk



## DECLARATION OF PERFORMANCE 39T032DPO (v5)

Name	Drywall to light screw, high density, Phillips 2, Phosphated, 3,9x32mm
Article number	39T032DPO
GTIN	8715274308012

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco UK Ltd., 630 Europe Boulevard, Warrington WA5 7YH,UK
Intended use	Mechanical fastener
Unique identification code	39T032DPO
DOP No	39T032DPO
Designated standard	EN 14566:2008+A1:2009
AVCP	4

Declared performances	
Essential characteristics for: 39T032DPO	Performance
Reaction to fire	A1
Flexural strength	Pass

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in England, Wales and Scotland (acc. to e Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and Construction Products (Amendment etc.) (EU Exit) Regulations 2020) under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENCO UK Ltd by:

Place and date of issue: Warrington, 02-06-2026

Lars Aa. Mortensen  
Technical Manager, KYOCERA SENCO EMEA

Additional information		
Screw diameter	$d$	3.9 mm
Head diameter	$d_h$	6.5 mm
Screw length	$L$	32 mm
Threaded/profiled length	$l_g$	27 mm
Inner threaded diameter	$d_i$	2.95 mm
Reaction to fire		A1