



MAKE IT LAST.

KYOCERA SENC0 UK Ltd.
630 Europa Boulevard
Gemini Business Park
Warrington WA5 7YH, United Kingdom
Tel: +44 (0) 1925 445566
info@kyocera-senco.co.uk
www.kyocera-senco.co.uk



DECLARATION OF PERFORMANCE NN24AABMR (v0)

Name	NN metalconnector ring 4,0x60mm
Article number	NN24AABMR
GTIN	8715274036540

Intended use/uses and identification of the construction product	
Manufacturer	Kyocera Senco UK Ltd., 630 Europe Boulevard, Warrington WA5 7YH,UK
Intended use	Dowel-type fastener
Unique identification code	NN24AABMR
DOP No	NN24AABMR
Designated standard	EN 14592:2008+A1:2012
AVCP	3
NB	1686

Declared performances		
Essential characteristics for: NN24AABMR		Performance
Characteristic yield moment	$M_{y,k}$	6850 Nmm
Characteristic withdrawal parameter	$f_{ax,k}$	6.99 N/mm ²
	$f_{head,k}$	NPD
Characteristic tensile capacity	$f_{tens,k}$	NPD
Durability against corrosion		Zinc Plated, SC 1, EN 1995-1-1

$f_{ax,k}$ en $f_{head,k}$ are tested at a characteristic timber density of 350 kg/m³

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in England, Wales and Scotland (acc. to e Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and Construction Products (Amendment etc.) (EU Exit) Regulations 2020) under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of KYOCERA SENC0 UK Ltd by:

Place and date of issue: Warrington,

Lars Aa. Mortensen
Technical Manager, KYOCERA SENC0 EMEA

Additional information		
Nail diameter	d	4 mm
Head cross sectional area	d_h	50 mm
Nail length	L	60 mm
Threaded/profiled length	l_g	53 mm
Length of point	L_p	5.1 mm
Coating type	Type	Coating type 3
Reaction to fire		A1