


GC SMOOTH STRIPNAIL 2,87X55MM CARBON STEEL STANDARD TENSILE



GC52AABKR

APPLICATIONS

Framing, sheathing, subfloor, decking, trusses, pallets and crates


TECHNICAL SPECIFICATIONS

Collation angle	34 °
Collation type	Paper collated
Wire material	Carbon steel standard tensile
Finish	Regular galvanised
Coating	Sencoted
Nail head type	Clipped head
Head width	6.81 - 7.21 mm
Head length	4.85 - 5.2 mm
Nail shank type	Smooth shank
Point type	Diamond
Pointangle	40 °
Nail length	55 mm
Nail diameter	2.87 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274043753
Package quantity	2000 pieces
Net weight	5.89 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

Dit veld moet nog verwijderd worden EN 14592:2008+A1:2012

CE fastener type Round cross-section plain shank nail

Protection level in micron ≤5

Service class 1

Coating type Coating type 3

Coating length 31 mm

Head cross sectional area 30 mm

Characteristic yield moment 3054 Nmm

Dit veld moet nog verwijderd worden 2.45 N/mm²

Characteristic head pull through parameter 27.12 N/mm²

Characteristic tensile strength 695 N/mm²