

SENCO CN CON. HDG DP SM PLAIN 3,1X38MM CARBON STEEL STANDARD TENSILE



HJ17ASAVR

APPLICATIONS

Asphalt shingles, fiber glass shingles, siding, vapor barriers


TECHNICAL SPECIFICATIONS

Collation angle	16 °
Wounding type	Conical
Collation type	Wire collated
Wire material	Carbon steel standard tensile
Finish	Hot-Dipped galvanised 3
Coating	Plain
Nail head type	Full round head
Nail shank type	Smooth shank
Point type	Diamond
Pointangle	40 °
First welding wire distance	14.2 - 15.5 mm
Second welding wire distance	33.5 - 34 mm
Nail length	38 mm
Nail diameter	3.1 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274054902
Package quantity	1800 pieces
Net weight	6 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

Dit veld moet nog verwijderd worden EN 14592:2008+A1:2012

CE fastener type Round cross-section plain shank nail

Protection level in micron 30

Service class 3

Coating type Coating type 3

Head cross sectional area 72 mm

Characteristic yield moment 3000 Nmm

Dit veld moet nog verwijderd worden 3.9 N/mm²

Characteristic head pull through parameter 25.5 N/mm²

Characteristic tensile strength 620 N/mm²