


SENCO CN CON F.GALV DP SM PLAIN 3,1X25MM CARBON STEEL STANDARD TENSILE



HJ13ATAV

APPLICATIONS

Asphalt shingles, fiber glass shingles, siding, vapor barriers


TECHNICAL SPECIFICATIONS

Collation angle	16 °
Wounding type	Conical
Collation type	Wire collated
Wire material	Carbon steel standard tensile
Finish	Flash galvanised or greater
Coating	Plain
Nail head type	Full round head
Nail shank type	Smooth shank
Point type	Diamond
Point angle	40 °
First welding wire distance	14.2 - 15.5 mm
Second welding wire distance	33.5 - 34 mm
Nail length	25 mm
Nail diameter	3.1 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274021775
Package quantity	7560 pieces
Net weight	11.61 kg

FASTENER SPECIFICATIONS



CE SPECIFICATIONS

CE fastener type	Round cross-section plain shank nail
Protection level in micron	≤5
Service class	1
Coating type	NA
Coating length	16.5 mm
Head cross sectional area	72 mm
Characteristic yield moment	3000 Nmm
Dit veld moet nog verwijderd worden	3.9 N/mm ²
Characteristic head pull through parameter	25.5 N/mm ²
Characteristic tensile strength	620 N/mm ²