


FLOORING/DECKING WOOD TO WOOD SCREW 4,2X55MM

CARBON STEEL STANDARD TENSILE



42W55MWN

APPLICATIONS

Wood-to-wood applications, decking, fencing

TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw recess	Senco drive 25
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Carbon steel standard tensile
Finish	Weatherex II
Point type	Type 17 cut point
Pointangle	23 °
Screw length	53.8 - 56.2 mm
Screw diameter	4.05 - 4.3 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274251844
Package quantity	4000 pieces

CE SPECIFICATIONS

Dit veld moet nog verwijderd worden	EN 14592:2008+A1:2012
Material notification on CE label	Non-alloy steel
Service class	3
Inner threaded diameter	3.15 mm
Threaded/profiled length	36.6 mm
Characteristic yield moment	3283 Nmm
Dit veld moet nog verwijderd worden	10.87 N/mm ²
Characteristic head pull through parameter	16 N/mm ²
Characteristic tensile strength	5112 N/mm ²
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.74 Nm
Characteristic torsional strength	3.47 Nm