


FLOORING WOOD TO WOOD SCREW 4,2X45MM CARBON STEEL STANDARD TENSILE



42R45MYN

APPLICATIONS

Wood-to-wood applications, subfloor

TECHNICAL SPECIFICATIONS

Collation type	Plastic collated
Screw head type	Small with 4 nibs
Screw recess	Phillips 2
Screw thread type	2/3 coarse
Rotations per minute	2300 RPM
Wire material	Carbon steel standard tensile
Finish	Yellow zinc
Point type	Type 17 cut point
Pointangle	23 °
Screw length	43.8 - 46.2 mm
Screw diameter	4.1 - 4.3 mm

LOGISTICAL SPECIFICATIONS

GTIN	8715274251820
Package quantity	4000 pieces

CE SPECIFICATIONS

Dit veld moet nog verwijderd worden	EN 14592:2008+A1:2012
Material notification on CE label	Non-alloy steel
Protection level in micron	3
Service class	1
Inner threaded diameter	2.95 mm
Threaded/profiled length	30 mm
Characteristic yield moment	3283 Nmm
Dit veld moet nog verwijderd worden	12.35 N/mm ²
Characteristic head pull through parameter	16 N/mm ²
Characteristic tensile strength	4504 N/mm ²
Torsional ratio	≥ 1,5
Characteristic torsional resistance	1.47 Nm
Characteristic torsional strength	3.47 Nm